

---

# Release Notes <WAP4 WinCE 6 OS Image><v4.0>

## Contents

---

[Description](#)

[Device Compatibility](#)

[Component Contents](#)

[Installation Requirements](#)

[Installation Instructions](#)

[Downloadable Software included in this Release](#)

## Description

---

The following changes and fixes have been included in Release 4.0:

<b>SPR NO</b>	<b>Synopsis</b>
N/A	Added support for ETSI RE-D compliance.
N/A	Update GPRS operator database.
32005	Improve WWAN radio detection on reboot.
30487	Fixed Total Recall archiving algorithm to prevent file corruption on restore.

The following issues have been resolved in CFE builds since Release 3.0.1:

<b>SPR NO</b>	<b>Synopsis</b>
27417	Fix automatic suspend when multiple Fusion profiles are configured but not connected.
28468	Restore Advanced Options tab in Scanner Services for SE1524 and SE965.
29173	Improve tether port detection algorithm
28682	Correct decoding of 2D QR codes
28835	Improve GPS receiver accuracy when device is stationary.
30174	Corrected behavior of Network LAN taskbar icon when using quad dock.
30320	Improve Battery Health indicator for batteries no longer supported or recognized.

30611	Allow the use of external Bluetooth GPS devices.
31726	Add ISO-8859-1 (Western Europe) encoding.

## Device Compatibility

---

This software release has been approved for use with the following Zebra devices.

Device	Operating System
Workabout Pro 4 (7528)	Windows CE 6.0 Professional

## Component Contents

---

N/A

## Installation Requirements

---

If previously installed, uninstall '7528 Release 2.3 OS Patch v1.1'.

## Installation Instructions

---

To **uninstall** 7528 Release 2.3 OS Patch v1.1, follow the procedure below:

1. Delete contents of \Application\Tiinit folder.
2. Clean start device or update operating system software.

To update the operating system software of the WAP 4, follow the procedure below:

1. **If previously installed, uninstall '7528 Release 2.3 OS Patch v1.1' (Instructions above).**
2. The firmware can be upgraded using a USB Memory Stick or using a microSD Card.
3. The firmware file must be renamed 7528os.img
4. Copy the file containing the firmware upgrade to the root directory of the USB memory stick or Micro SD card
5. Install the USB memory stick into the docking cradle or install the Micro SD card into the WAP 4 in the Micro SD slot in the battery compartment
6. Press and hold down the [Blue FN] key, the [SCAN] key and the [Power] key, simultaneously for a minimum of six seconds.
7. When the update is complete, the device reboots to the main operating system.

8. Remove the MicroSD card from the device to prevent the device from performing the upgrade process again on the next cold boot, and then disconnect external power. The device is now ready to be used.

## Downloadable Software Included in this Release

---

Filename	Description
P728XC60EFMI040000.IMG	WAP4 Windows CE OS image CFE ENG/FRA/GER/ITA/ESN v4.0
P728XC60CTMI040000.IMG	WAP4 Windows CE OS image CFE TRADITIONAL CHINESE v4.0
P728XC60CPMI040000.IMG	WAP4 Windows CE OS image CFE SIMPLIFIED CHINESE v4.0
P728XC60JPMI040000.IMG	WAP4 Windows CE OS image CFE JAPANESE v4.0
P728XC60KOMI040000.IMG	WAP4 Windows CE OS image CFE KOREAN v4.0

Last Revised: 5/25/2017